

# A COMPACT AND INTUITIVE MULTIFUNCTION DEVICE FOR SEAMLESS WORKFLOWS.

Multifunction A4 colour devices  
for smooth and speedy printing  
processes, designed for ease of use in  
smaller workspaces.

## i-SENSYS MF750 II Series



### HIGH-QUALITY PRINTING

Produce high-quality output from toners with a wide range of colours and achieve bright, vibrant prints with excellent reproduction of both light and dark tones.

### SMOOTH USER EXPERIENCE

Use the intuitive UI to easily carry out a range of printing and scanning tasks and quickly reach relevant parts of the online manual via a QR code. Save time with the Master set up which automatically downloads and installs software.

### 360-DEGREE SECURITY

A Security Settings Navigator recommends appropriate security settings to protect against security leaks and cyber threats.

### IMPROVE SUSTAINABILITY EFFORTS

Increase your sustainability efforts by embracing devices that use recycled plastic and cardboard packaging for toner cartridges.

### GREATER PRODUCTIVITY

Boost collaboration and productivity with speedy printing and scanning. Scan small size documents with ease including cheques and receipts.

# TECHNICAL SPECIFICATIONS

MAIN UNIT	
Machine type	Colour Laser All-In-One
Available functions	Print, Copy, Scan and Fax
PRINTER	
Print speed	Single sided : Up to 33 ppm (A4) Up to 60 ppm (A5-Landscape) Double sided : Up to 29.5 ipm (A4)
Printing method	Colour laser beam printing
Print resolution	Up to 1200 x 1200 dpi
Warm-up time	Approx. 14 seconds or less from power on
Printer languages	i-SENSYS MF752Cdw II : UFR II, PCL 5c <sup>2</sup> , PCL6 i-SENSYS MF754Cdw II : UFR II, PCL 5c <sup>2</sup> , PCL6, Adobe® PostScript <sup>3</sup>
Fonts	i-SENSYS MF752Cdw II : 45 PCL fonts i-SENSYS MF754Cdw II : 45 PCL fonts, 136 PostScript fonts
Print margins	5 mm-top, bottom, left and right 10 mm-top, bottom, left and right (Envelope)
Toner saver mode	Yes
Advanced printing features	Encrypted Secure Print Secure Print Print from USB memory key (JPEG/TIFF/PDF) Print from Cloud (Dropbox, GoogleDrive, OneDrive) (PDF/JPEG) Microsoft Universal Print support iOS: AirPrint, Canon PRINT app Android; Mopria certified, Canon Print Service Plug-in, Canon PRINT app, IPP everywhere
COPIER	
Copy speed	Single sided (A4): Up to 33 ppm Double sided (A4): Up to 29 ipm
First Copy Output Time (FCOT)	ADF (A4): Colour Approx. 8.8 seconds or less Mono Approx. 7.6 seconds or less Platen (A4): Colour Approx. 9.4 seconds or less Mono Approx. 8.3 seconds or less
Copy resolution	Up to 600 x 600 dpi
Copy modes	Text/Photo/Map (Default), Text/Photo/Map (quality), Printed Image, Text
Double sided copying	2-sided to 2-sided (Automatic)
Multiple copy	Up to 999 copies
Reduction / Enlargement	25-400% in 1% increments
Other features	Preset R/E Ratios by Area, Two-Sided, Density Adjustment, Original Type Selection, Two-sided Original, Sort, N on 1, Sharpness, Erase Frame, Copy ID Card, Copy Passport, Color Mode, Reserved copy
SCANNER	
Type	Colour
Scan resolution	Optical: Up to 600 x 600 dpi Enhanced: Up to 9600 x 9600 dpi
Scan speed	Single sided mono: 50ipm (300x300dpi) Single sided colour: 40ipm (300x300dpi) Double sided mono: 100ipm (300x300dpi) Double sided colour: 80ipm (300x300dpi) Single sided mono: 40ipm (300x600dpi) Single sided colour: 20ipm (300x600dpi) Double sided mono: 80ipm (300x600dpi) Double sided colour: 40ipm (300x600dpi)
Colour scanning depth	24 bit/24 bit (input/output)
Greyscales	256 levels
Compatibility	TWAIN, WIA, ICA
Max. scan width	216mm
Scan to E-mail	TIFF/JPEG/PDF/Compact PDF/Searchable PDF / PDF/A-1b
Scan to PC	TIFF/JPEG/PDF/Compact PDF/Searchable PDF / PDF/A-1b

# i-SENSYS MF750 II Series

Scan to USB memory key	TIFF/JPEG/PDF/Compact PDF/Searchable PDF / PDF/A-1b
Scan to FTP	TIFF/JPEG/PDF/Compact PDF/Searchable PDF / PDF/A-1b
Scan to Cloud <sup>1</sup>	TIFF/JPEG/PDF/PNG <sup>3</sup>
iFAX	i-SENSYS MF754Cdw II : ITU-T.37
FAX (i-SENSYS MF754Cdw II only)	
Modem speed	33.6 Kbps (Up to 3 seconds/page <sup>4</sup> )
Receive mode	Fax only, Fax/Tel Auto Switch, Answer Mode, Manual
Fax resolution	Standard: 200 x 100 dpi Fine: 200 x 200 dpi Super fine: 200 x 400 dpi Ultra fine: 400 x 400 dpi
FAX memory	Up to 512 pages <sup>4</sup>
Speed dials	Up to 281 dials
Group dials/destinations	Max. 299 dials / Max. 299 destinations
Sequential broadcast	Max. 310 destinations
Memory backup	Permanent fax memory backup (Backup with flash memory)
Double sided faxing	Yes (Transmit and Receive)
Other features	Sender's Name (TTI), Direct Send, Preview, TX Report, Sequential Broadcasting
MEDIA HANDLING	
Scanner type	Platen, 2-sided ADF (single pass)
Paper input (Standard)	250 sheets 50 sheets 50 sheets
Paper input (Option)	550 sheets
Maximum paper input capacity	850 sheets
Paper output	150 sheets
Media types	Plain paper, Recycled paper, Heavy Paper, Thin paper, Colour paper, Coated paper, Pre-punched, Label, Post card, Envelope
Media sizes	Cassette (Standard): A4, A5, A5 (Landscape), A6, B5, Legal, Letter, Executive, Statement, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, Foolscap, 16K, Post card, Envelop (COM10, DL, C5, Monarch), Custom sizes: Min. 98 x 148 mm Max. 216.0 x 356.0 mm.  Multi-purpose tray: A4, A5, A5 (Landscape), A6, B5, Legal, Letter, Executive, Statement, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, Foolscap, 16K, Post card, Indexcard, Envelope (COM10, DL, C5, Monarch), Custom sizes: Min 76.0 x 127 mm Max. 216.0 x 356.0 mm.  Cassette (Optional): A4, A5, A5 (Landscape), A6, B5, Legal, Letter, Executive, Statement, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, Foolscap, 16K, Post card, Custom sizes: Min. 100 x 148 mm Max. 216.0 x 356.0 mm.  ADF: A4, A5, A6, B5, Legal, Letter, Statement, Custom sizes: Min. 48 x 85.0 mm Max 216.0 x 355.6 mm
Media weights	Cassette (standard and optional): 60 to 163 g/m <sup>2</sup> (Up to 200 g/m <sup>2</sup> with Coated paper) Multi-purpose tray: 60 to 176 g/m <sup>2</sup> (Up to 200 g/m <sup>2</sup> with Coated paper) ADF: 50 to 105 g/m <sup>2</sup>

# TECHNICAL SPECIFICATIONS

<b>Double sided printing</b>	Automatic Cassette: A4, A5, B5, Legal, Letter, Executive, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, Foolscap, 16K Custom size - Min. 148 x 148 mm Max. 216 x 356 mm 60 to 200 g/m <sup>2</sup>
<b>INTERFACE &amp; SOFTWARE</b>	
<b>Interface type</b>	USB 2.0 Hi-Speed, 10BASE-T/100BASE-TX/1000Base-T, Wireless 802.11b/g/n, Wireless Direct Connection
<b>Operating System compatibility</b>	Windows® 11 / Windows® 10 / Server® 2025 / Server® 2022 / Server® 2019 / Server® 2016 Mac OS X version 10.15 & up Linux <sup>5</sup>
<b>Network Protocol</b>	Print: TCP/IP (LPD/Port9100/IPP/IPPS/WSD)
	Scan: Push Scan: File: FTP (TCP/IP), SMB3.1.1 (TCP/IP) E-mail/Fax: SMTP (send), POP3 (receive) Pull Scan: TCP/IP
	Management: SNMPv1, SNMPv3 (IPv4,IPv6)
	Security: TLS1.3, IPSec, IP address filtering, IEEE802.1X, SNMPv3, SSL (HTTPS, IPPS) Security (wireless): Infrastructure Mode: WPA-PSK(AES), WPA2-PSK(AES), WPA3-SAE (AES), WPA-EAP(AES), WPA2-EAP(AES), WPA3-EAP(AES) Access Point Mode: WPA2-PSK(AES), WPA3-SAE (AES)
<b>Software and printer management</b>	MF Scan Utility, Remote User Interface (RUI), Department ID Management, Toner Status Tool, iW Enterprise Management Console: Server-based software for centralised management of a fleet of devices Cooperating with External Security Audit System (Security Information and Event Management) eMaintenance: embedded RDS allows remote eMaintenance services such as meter capture, automatic consumables management and remote diagnostics. Application Library
<b>GENERAL FEATURES</b>	
<b>Processor Speed</b>	1200MHz
<b>Memory</b>	1GB
<b>Storage</b>	4GB
<b>Control panel</b>	12.7 cm LCD Colour Touch Screen
<b>Dimensions with trays (W x D x H)</b>	425 mm x 461 mm x 430 mm
<b>Installation space (W x D x H)</b>	625 mm x 1,117 mm x 990 mm
<b>Weight</b>	i-SENSYS MF752Cdw II : Approx. 23.30 Kg i-SENSYS MF754Cdw II : Approx. 23.60 Kg
<b>Operating environment</b>	Temperature: 10 to 30°C (50 to 86°F) Humidity: 20 to 80% RH (no condensation)
<b>Power Source</b>	220-240V(±10%) 50/60Hz (±2Hz)
<b>Power Consumption</b>	Maximum: Approx. 1,380 W Active printing: Approx. 700W Standby: Approx. 24.0 W Sleep mode: Approx. 1.0 W Typical Electricity Consumption (TEC): 0.30 kWh/week <sup>9</sup> (230V) For detailed information relating to Lot26 regulation, please go to: <a href="http://www.canon-europe.com/For_Work/Lot26/index.aspx">http://www.canon-europe.com/For_Work/Lot26/index.aspx</a>

# i-SENSYS MF750 II Series

<b>Noise Levels</b>	Sound Pressure <sup>6</sup> : Active: Simplex 51dB / Duplex 51dB (BW), 50dB (CL) Standby: 29 dB
	Sound Power <sup>6</sup> : Active: 65dB or less Standby: 41dB or less
<b>CONSUMABLES</b>	
<b>Cartridges</b>	Cartridge 069 Black (2,100 pages <sup>7)8</sup> Cartridge 069H Black (7,600 pages <sup>7)8</sup> Cartridge 069 Cyan (1,900 pages <sup>7)8</sup> Cartridge 069H Cyan (5,500 pages <sup>7)8</sup> Cartridge 069 Magenta (1,900 pages <sup>7)8</sup> Cartridge 069H Magenta (5,500 pages <sup>7)8</sup> Cartridge 069 Yellow (1,900 pages <sup>7)8</sup> Cartridge 069H Yellow (5,500 pages <sup>7)8</sup>
<b>ACCESSORIES/ OPTIONS</b>	
<b>Items</b>	i-SENSYS MF752Cdw II : PAPER FEEDER PF-K1 (550-sheet cassette) i-SENSYS MF754Cdw II : PAPER FEEDER PF-K1 (550-sheet cassette) TEL 6 Kit Long Cord (Telephone handset)

## Notes:

- Subscription to a third party cloud service is required, and subject to their party terms and conditions.
- Commands supported only. Third party driver or direct printing from application required.
- Scan by MF Scan Utility or Canon PRINT
- Based on ITU-T Standard Chart No. 1
- Web distribution only. Linux support printing only.
- Declared noise emission in accordance with ISO 7779.
- Based on ISO/IEC 19798
- Printer ships with Black: 2,100 pages, C/M/Y: 1,100 pages starter cartridges
- As per US ENERGY STAR® version 3.2.

# i-SENSYS MF750 II Series



**Canon Inc.**  
Canon.com

**Canon Europe**  
canon-europe.com

**English Edition**  
© Canon Europa N.V. 2025