

imagePRESS C270 Series

PUSH YOUR CREATIVE LIMITS AND DO MORE

Ideal for any business environment, this intuitive and powerful device easily handles your day-to-day document workflows while also giving you the option to print high quality marketing materials.



- **HIGH QUALITY**

Outstanding image quality with image PRESS R-VCSEL technology and 2400 x 2400 dpi print resolution
Day-after-day consistent colour with Multi-Density Adjustment Technology (Multi DAT)
Accurate front-to-back registration for precise double-sided image quality

- **VERSATILITY**

Improved media handling supporting multiple paper sizes, weights and types, up to 350gsm media and an unique long-sheet functionality, plus high-capacity finishing options

- **COST EFFECTIVENESS**

Deliver professional quality print in-house quickly with full control and lower costs
Track and control usage with print management software including uniflow

- **USER EXPERIENCE**

Intuitive user interface like imageRUNNER ADVANCE range, supporting office functionality
Integrated timeline for efficient digitisation with one-touch workflows and swift access to shortcut buttons on Home screen

- **CONNECTIVITY**

Easy cloud connectivity to securely scan and print documents from anywhere
Multi-functional Embedded Application Platform (MEAP) ready platform
Automated printing on-demand with uniFLOW software

- **RELIABLE SECURITY**

Advanced protection for your documents, device and network including McAfee Embedded Control, encrypted SSD, Verify system at start-up, Syslog – SIEM Integration, and Access management Control
Always up-to-date security features including TLS1.3 and TPM2.0

Canon

TECHNICAL SPECIFICATIONS

imagePRESS C270 Series

MAIN UNIT

Machine type	A3 Colour Laser Multifunctional
Core functions	Print, Copy, Scan, Send, Store and Optional Fax
Processor	1.8GHz Dual Core Processor
Control panel	10.1" (25.6 cm) TFT LCD WSVGA Colour Touch panel
Memory	Standard: 5.0GB RAM
Storage	Standard: (SSD) 256GB Optional: (SSD) 1TB
Interface Connection	NETWORK Standard: 1000Base-T/100Base-TX/10Base-T, Wireless LAN(IEEE 802.11 b/g/n) Optional: Bluetooth Low Energy OTHERS Standard: USB 2.0(Host) x1, USB 3.0(Host) x1, USB 2.0(Device) x1 Optional: Serial Interface, Copy Control Interface
Paper supply capacity (A4, 80gsm)	Standard: 3,550 sheets 250-sheet Multi-purpose tray, 1100-sheet Paper Deck x 2, 550-sheet Paper Cassette x 2 Maximum: 7,050 sheets (with Paper Deck Unit-E1 or POD Deck Lite-C1)
Paper output capacity (A4, 80gsm)	250 sheets (with Copy Tray-R2) Maximum: 3,500 Sheets (with Staple Finisher-AC1 or Booklet Finisher-AC1) Maximum: 5,000 Sheets (with Staple Finisher-AG1 or Booklet Finisher AG1)
Finishing capabilities	With options: Collate, Group, Offset, Staple, Saddle Stitch, Hole Punch, Eco Staple, Staple On Demand, Document Insertion, Z-fold, Half-fold, C-fold, Accordion-Z fold, Double Parallel-fold, Trimming

Supported media types	<u>Multi-purpose tray:</u> Thin, Plain, Recycled, Color, Heavy, Coated, Textured, Tracing, Bond, Transparency, Label, Pre-punched, Letterhead, Tab, Envelope <u>Paper Decks (Right/Left):</u> Thin, Plain, Recycled, Color, Heavy, Tracing, Bond, Transparency, Pre-punched, Letterhead <u>Paper Cassettes (Upper/Lower):</u> Thin, Plain, Recycled, Color, Heavy, Bond, Transparency, Pre-punched, Letterhead, Tab ¹ , Envelope ²
------------------------------	---

¹ Tab Feeding Attachment-F1 is required
² Envelope Feeder Attachment-F1 is required.

Supported media sizes	<u>Multi-purpose tray:</u> Standard size: SRA3, A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R Custom size: 90.0 x 148.0 mm to 330.2 x 487.7 mm Long size: 210.0x487.8 mm to 330.2x1,300.0mm ¹ Free size: 100.0 x 148.0 mm to 330.2 x 487.7 mm Envelope: COM10 No.10, Monarch, DL, ISO-C5 Envelope custom size: 90.0 x 148 mm to 330.2 x 487.7 mm. ¹ by service mode <u>Paper Decks (Right/Left):</u> Standard size: A4, B5 <u>Paper Cassettes (Upper/Lower):</u> Standard size: SRA3, A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R Custom size: 139.7 x 182.0mm to 330.2 x 487.7mm Envelope: COM10 No.10, Monarch, DL, ISO-C5 Envelope custom size: 98.0 x 148.0mm to 330.2 x 487.7mm
------------------------------	---

Supported media weights	Multi-purpose tray: 52 to 350 gsm Paper Decks (Right/Left): 52-220 gsm Paper Cassettes (Upper/Lower): 52-256 gsm Multi-purpose tray: 52-350 gsm Optional PAPER DECK UNIT-E1: 52-256 gsm Optional POD DECK LITE-C1: 52-350 gsm Optional STACK BYPASS-D1: 52-350 gsm Duplex: 52-220 gsm
--------------------------------	--

Warm-up time	Quick Startup Mode: 4 seconds or less (Time until key operations can be performed on the touch panel display) From Power On: 30 seconds or less (Time until it becomes possible to start copying) From Sleep Mode: 30 seconds or less
---------------------	---

Dimensions (W x D x H)	689 x 937 x 1,185 mm
Weight	Approx. 261 kg (including toner)

PRINT SPECIFICATIONS

Print speed (CL/BW)	C270 70 ppm CL and 80 ppm BW (A4, A5*, A5R, A6R*) 35 ppm CL and 40 ppm BW (A3), 49 ppm CL and 56 ppm BW *A5/A6R (1-sided) C265 65 ppm CL and 70 ppm BW (A4, A5*, A5R, A6R*) 32 ppm CL and 35 ppm BW (A3), 46 ppm CL and 49 ppm BW
Target (Max) print/copy volume per month	Up to 100,000 pages
Monthly duty cycle	C270 390,000 pages C265 330,000 pages
Front-back registration	Cross track: 2.0 mm or less, In track: 1.2mm or less
Printing method	Colour Laser Beam Printing (Electronic Photography)
Print resolution (dpi)	2,400 x 2,400
Page description languages	UFR II, PCL6, (optional) imagePRESS PS Printer Kit-G1

Direct print

Direct printing available from USB memory, Advanced Space, Remote UI and Web Access*
Supported file types: TIFF, JPEG, PDF, EPS and XPS

Printing from mobile and cloud

*Only PDF print from websites is supported

AirPrint, Mopria, Canon PRINT Business, uniFLOW Online and Universal Print

A range of software and MEAP-based solutions are available to provide printing from mobile devices or internet-connected devices and cloud-based services depending on your requirements.
Please contact your sales representative for further information.

Fonts

PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts, Andalé Mono WT J/K/S/T* (Japanese, Korean, Simplified and Traditional Chinese), Barcode fonts**

*Requires optional PCL INTERNATIONAL FONT SET-A1

**Requires optional BARCODE PRINTING KIT-D1

Print Features

PS fonts: 136 styles

Secured Print, Secure Watermark, Header/Footer, Page Layout, Two-sided Printing, Mixed Paper Sizes/Orientations, Front/Back Covers, Toner Reduction, Poster Printing, Forced hold printing, Print Date, Scheduled Printing, Printing Using a Virtual Printer

Operating System

UFR II: Windows* 8.1/10/11/Server2012/Server2012 R2/Server2016/Server2019/Server2022, Mac OS X (10.11 or later)

PCL: Windows* 8.1/10/11/Server2012/Server2012 R2/Server2016/Server2019/Server2022

PS: Windows* 8.1/10/11/Server2012/Server2012 R2/Server2016/Server2019/Server2022, Mac OS X (10.11 or later)

PPD: Windows* 8.1/10/11, Mac OS X(10.11 or later)

COPY SPECIFICATIONS

Copy speed (CL/BW)

C270

70 ppm CL and 80 ppm
BW (A4, A5*, A5R, A6R*).
35 ppm CL and 40 ppm
BW (A3), 49 ppm CL and
56 ppm BW

*1-sided

C265

65 ppm CL and 70 ppm BW
(A4, A5*, A5R, A6R*).
32 ppm CL and 35 ppm BW
(A3), 46 ppm CL and 49
ppm BW

*1-sided

First-Copy-Out Time (A4) (BW/CL)

C270
Approx. 4.4/5.4 seconds
or less

C265
Approx. 4.8/5.9 seconds
or less

Copy resolution (dpi)

600 x 600

Multiple Copies

Up to 9,999 copies

Copy density

Automatic or Manual (9 Levels)

Magnification

25% - 400% (1% Increments)

Preset reductions

25%, 50%, 70%, 100% (1:1)

Preset enlargements

141%, 200%, 400%

Copy Features

Preset R/E Ratios by Area, Two-Sided, Density Adjustment, Original Type Selection, Interrupt Mode, Book to Two Pages, Two-sided Original, Job Build, N on 1, Add Cover, Insert Sheets, Different Size Originals, Page Numbering, Copy Set Numbering, Sharpness, Erase Frame, Secure Watermark, Print Date, Gutter, Print & Check, Negative/Positive, Repeat Images, Merge Job Blocks, Mirror Image, Store in Mail Box, Superimpose Image, Copy ID Card, Skip Blank Pages, Free Size Original, Color Mode, Reserved copy, Copy Sample

SCAN SPECIFICATIONS

Type

Single-pass Duplexing Automatic
Document Feeder* [2-sided to 2-sided (Automatic)]

Document Feeder paper capacity (80 gsm)

*Detect Feeder Multi Sheet Feed is supported.

200 Sheets

Acceptable originals and weights

Platen: Sheet, Book, 3-Dimensional objects
Document Feeder media weight:
1-sided scanning: 38 to 220 gsm (BW, CL)
2-sided scanning: 38 to 220 gsm (BW, CL)

*An acceptable weights of A6R or smaller is 50 to 220gsm.

Supported media sizes

Platen: max. scanning size: 297.0 x 431.8 mm
Document Feeder media size: A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R, B6R, Custom size (70.0 x 139.7 mm to 304.8 x 431.8 mm)

Scan speed (ipm: BW/CL; A4)

Single-sided Scanning: 135/135 (300 x 300 dpi, send), 80/80 (600 x 600 dpi, copy),
Double-sided Scanning: 270/270 (300 x 300 dpi, send), 160/90 (600 x 600 dpi, copy)

Scan resolution (dpi)

600 x 600

Pull Scan specifications

Colour Network ScanGear2 for both TWAIN and WIA
Supported OS: Windows* 8.1/10/Server2012/Server2012 R2/Server 2016/Server 2019
As of Oct. 2021

Scan method

Push Scan, Pull Scan, Scan to Box, Scan to Advanced Space, Scan to Network, Scan to USB Memory Key, Scan to Mobile devices, Scan to cloud (uniFLOW Online)

SEND SPECIFICATIONS

Destination

E-mail/Internet FAX (SMTP), SMB v3.0, FTP, WebDAV, Mail Box, Super G3 FAX (Optional), IP Fax (Optional)

Address book

LDAP (2,000), Local (1,600), Speed dial (200)

Send resolution (dpi)

600 x 600

Communication protocol

File: FTP (TCP/IP), SMB v3.0, WebDAV
E-mail/I-Fax: SMTP, POP3



TECHNICAL SPECIFICATIONS

imagePRESS C270 Series

File format	TIFF, JPEG, PDF (Compact, Searchable, Apply policy, Optimize for Web, PDF/A-1b, Trace & Smooth, Encrypted, Device Signature, User Signature), XPS (Compact, Searchable, Device Signature, User Signature), Office Open XML (PowerPoint, Word)	Plug (Main Unit)	C270 Approx. 2,500 W C265 Approx. 2,000 W; Copying: (with DADF continuous scan) Approx. 1,228 W* Standby: Approx. 136.6 W** Sleep mode: Approx. 0.9 W* * Reference value: measured by only one unit. ** 0.9W sleep mode is not always available in all circumstances due to certain settings.
Universal Send Features	Original Type Selection, Two-sided Original, Book to Two Pages, Different-size Originals, Density Adjustment, Sharpness, Copy Ratio, Erase Frame, Job Build, Delayed Send, Preview, Job Done Notice, File Name, Subject/Message, Reply-to, E-mail Priority, TX Report, Original Content Orientation, Skip Blank Pages	Power consumption	
FAX SPECIFICATIONS		Noise levels (BW/CL)	Sound Power Level (LWA,m) Active (BW) (1-sided) C270: 7.0 B*, Kv 0.3 B* C265: 7.0 B*, Kv 0.3 B* *Reference value: measured only one unit with ISO7779, described with ISO9296 (2017)
Maximum number of connection lines	1		Sound Pressure (LpAm) Bystander's position: Active (BW/CL) (1-sided) C270: 56 dB*/56 dB* C265: 55 dB*/55 dB* Stand-by C270/C265: 35 dB* * Reference value: measured only one unit with ISO7779, described with ISO9296 (2017)
Modem speed	Super G3: 33.6 kbps G3: 14.4 kbps	Standards	Blue Angel
Compression method	MH, MR, MMR, JBIG	CONSUMABLES	
Resolution (dpi)	400 x 400 (Ultra Fine), 200 x 400 (Super Fine), 200 x 200 (Fine), 200 x 100 (Normal)	Toner cartridges	T-07 TONER BK/C/M/Y
FAX memory	Up to 30,000 pages (2,000 jobs)	Toner Yield (Estimated @ 8.5% Coverage)	Toner T07 BK: 54,500 pages Toner T07 C/M/Y: 37,500 pages
Group dials/destinations	Max. 199 dials	SOFTWARE AND PRINTER MANAGEMENT	
Sequential broadcast	Max. 256 addresses	Tracking and reporting	Universal Login Manager (ULM) uniFLOW Online Express
Memory backup	Yes	Remote management tools	iWEMC (iW Enterprise Management Console) eMaintenance Content Delivery System Color Network ScanGear 2 Canon Driver Configuration Tool MEAP (Multifunctional Embedded Application Platform)
Fax Features	Sender's Name (TTI), Selecting the Telephone Line (when sending fax), Direct Send, Delayed Send, Preview, Job Done Notice, TX Report, Interrupt Transmission, Sequential Broadcasting, Password/Subaddress Sending, Confidential Mailbox, 2 on 1 Log	Scanning software	
STORE SPECIFICATIONS		Optimisation tools	
Mail Box (Number supported)	100 User Inboxes, 1 Memory RX Inbox, 50 Confidential Fax Inboxes 30,000 (2,000 jobs) Maximum Pages Stored	Platform	
Advanced Space	Communication Protocol: SMB or WebDAV Supported Client PC: Windows* 8.1/10 Concurrent Connections (Max.): SMB:64, WebDAV:3	FIERY PRINT CONTROLLER SPECIFICATIONS	
Advanced Space available disc space	Approx. 16 GB Approx. 480 GB (with optional 1 TB SSD)	Optional/Standard	Optional
Advanced Space features	Authentication for Advanced Space Log-in, Sort Function, Printing a PDF File with a Password, imageWARE Secure Audit Manager Support, Search, File Preview, Authentication Management, Open to public, URI TX, Backup/Restore	Name	imagePRESS Server M20 (Embedded)
SECURITY SPECIFICATIONS		Print resolution (dpi)	1200 x 1200, 600 x 600
Authentication & Access Control	User Authentication (Picture Login, Picture and PIN Login, Card Login, Username and Password Login, Function Level Login, Mobile Login), Department ID Authentication (Department ID and PIN Login, Function Level Login), uniFLOW Online Express (PIN Login, Picture Login, Picture and PIN Login, Card Login, Card and PIN Login, Username and Password Login, Department ID and PIN Login, Function Level Login), Access Management System (Access Control)	Page Description Language(s)	Adobe PS3, PCL6
Document Security	Print Security (Secure Print, Encrypted Secure Print, Forced Hold Printing, uniFLOW Secure Print*), Receive Data Security (Confidential Fax Inbox Forwarding Received Documents Automatically), Scan Security (Encrypted PDF, Device Signature PDF/XPS, User Signature PDF/XPS, Adobe LiveCycle® Rights Management ES2.5 Integration), BOX Security (Mail Box Password Protected, Advanced Space Access Control), Send Data Security (Setting for requesting password input per transmission, Restricted E-mail/File send functions, Confirming FAX number, Allow/Restrict Fax Driver Transmissions, Allow/Restrict Sending from History, S/MIME Support), Document Tracking (Secure Watermark) **Requires uniFLOW Online / uniFLOW	Memory	8 GB (2 x 4 GB)
Network Security	TLS 1.3, IPsec, IEEE802.1X authentication, SNMP V3.0, Firewall Functionality (IP/MAC Address Filtering), Dual Network Support (Wired LAN/Wireless LAN, Wired LAN/Wired LAN), Disabling Unused Functions (Enabling/Disabling Protocols/Applications, Enabling/Disabling Remote UI, Enabling/Disabling USB Interface), G3 FAX separation from LAN, WPA3, USB Port separation from LAN, Prohibit the execution of files stored in Advanced Box in the MFP, Scan and Send -Virus Concerns for E-mail Reception	Hard Disk Drive	500 GB SATA
Device Security	Protecting SSD Data [SSD Data Encryption (FIPS140-2 Validated), SSD Lock], Standard SSD Initialize, Trusted Platform Module (TPM), Job Log Conceal Function, Protecting MFD Software Integrity, Checking MFP Software Integrity (Verify System at Startup, Runtime Intrusion Detection), Common Criteria Certification (HCD-PP: pending confirmation)	Processor speed	Intel Pentium G5400 (3.7 GHz)
Device Management and Auditing	Administrator Password, Digital Certificate And Key Management, Audit Log, Cooperating with External Security Audit System (Security Information and Event Management), Image Data Logging, Security Policy Setting	System	Fiery F5500
ENVIRONMENTAL SPECIFICATIONS		Fonts	PS: 138 Fonts PCL: 113 Fonts
Operating environment	Temperature: 20-27 °C Humidity: 15-60 % RH (Relative Humidity without condensation)	Supported Operating Systems	Windows* 7 64 bit/Windows 8.1 64 bit/Windows10 64 bit/Windows11/Windows Server 2008 R2 64bit only/Windows Server 2012 64bit only/Windows Server 2012 R2 64bit only/Windows Server 2016 64bit/Windows Server 2019 64bit/Windows Server 2022 64bit/ MAC OS (10.14, 10.15, 11.0, 12)
Power source	C270: 220-240 V (±10 %), 50/60 Hz (±2 Hz), 11 Amp C265: 220-240 V (±10 %), 50/60 Hz (±2 Hz), 10 Amp	Interface	2 x Ethernet (1000Base-T/100Base-TX/10Base-T), USB3.0 x 2 (Rear), USB2.0 x 4 (Rear)
		Network protocols	TCP/IP (FTP, SMTP, POP, HTTP, SNMP, LDAP, SLP, SMB, LPD, IPP, WS-Discovery, Bonjour, Direct Mobile Printing, Port9100, SNT, 802.1X, DHCP, DNS, NTP)
		Direct print	PDF1.7, EPS, TIFF6, JDF1.4/JMF (Optional)
		VDP	FreeForm v1/v2.1
		Fiery print controller standard features	Fiery Command WorkStation6 / Paper Catalog / Fiery Spot-On / Fiery Remote Scan / Fiery Hot Folders & Virtual Printers
		Fiery print controller options	Fiery Impose / Fiery Compose / Fiery Impose and Compose / Fiery Job Expert and PDF Processing Kit
		Hardware platform	E500
		Base OS	Debian of Linux
		Power source	AC100-240V, 50HZ/60HZ, 3.0A (100V) - 1.3A (240V)
		Maximum Power consumption	55 W
		Dimensions (W x D x H)	297 x 90 x 272 mm
		Weight	Fiery unit only (with plate): Approx. 5.5 kg
		PAPER SUPPLY OPTIONS	
		Paper Deck Unit-E1	Paper Capacity: 3,500 sheets (80 gsm) Paper Type: Thin, Plain, Recycled, Thick, Colour, Pre-punched, Letterhead, Bond Paper Size: A4, B5, LTR* Paper Weight: 52-256 gsm Power Source: From the main unit Dimensions (W x D x H): 340 x 630 x 572 mm (attached to the main unit) Weight: Approx. 34 kg *Media size change requires service technicians

TECHNICAL SPECIFICATIONS

imagePRESS C270 Series

POD Deck Lite-C1

Paper Capacity: 3,500 sheets (80 gsm)
 Paper Type: Thin, Plain, Recycled, Thick, Colour, Pre-punched, Letterhead, Bond, Tab, Transparency, Label, Coated, Textured, Tracing, Envelope*
 Paper Size: A3, B4, A4, A4R, B5, B5R, A5R, SRA3, 11"x17", LGL_R, LTR, LTR_R, EXE, STMT_R, 12"x18", 13"x19", 8K, 16K, 16K_R, Envelope [No.10(COM10), Monarch, DL, ISO-C5], Custom size (139.7 x 148.0 mm to 330.2 x 487.7 mm)
 Paper Weight: 52-350 gsm
 Power Source: 220-240V, 50/60Hz, 1.2A
 Dimensions (W x D x H): 633 x 686 x 574 mm (attached to the main unit) Weight: Approx. 68 kg
 *Requires ENVELOPE FEEDER ATTACHMENT-G1

OUTPUT OPTIONS

Copy Tray-R2

Provides a simple tray for basic output needs.
 Capacity: 250/100 sheets (1-sided/2-sided, 80 gsm)

Staple Finisher-AC1 (External)

Lower Tray (A) Capacity:
 A4/A5R/B5 3,000 sheets (80 gsm), SRA3/A3/A4R/B4/B5R/13"x19" 1,500 sheets (80 gsm), A6R 250 sheets*1 (80-105 gsm), Envelope 30/100 sheets (Monarch/Others), Long sheet** (Over 487.7 mm up to 762 mm length) 100 sheets (79 gsm),
 Long sheet** (Over 762 mm length) 1 sheet (holding by hand), All size of thin paper (52-63 gsm) 1,500 sheets,
 Capacity for coated paper is half of that for plain paper
 *1 A6R 50 sheets (106 gsm and above)
 ** Optional LONG SHEET TRAY-B1 is required

Upper Tray (B) Capacity:
 A4/A5R/B5 250 sheets (80 gsm), SRA3/A3/A4R/B4/B5R/13"x19" 125 sheets (80 gsm)
 Mid Tray (C) Capacity:
 A4/A5R/B5 250 sheets (80 gsm), SRA3/A3/A4R/B4/B5R/13"x19" 125 sheets (80 gsm)
 Paper Weight for Tray A:
 <Non Sort> 52-350 gsm, <Bunch Shift and Staple> 52-256 gsm*, <Eco Staple> 52-105 gsm
 *Excluding duplex printed thin paper (52-63 gsm) and any special media (Tracing, Transparency, Label)
 Paper Weight for Tray B/C:
 <Non Sort and Bunch Shift> 52-256 gsm*
 *Excluding duplex printed thin paper (52-63 gsm)
 Staple Position: Corner, Double
 Staple Capacity: <Non coated media, 52-90 gsm> A4 65 sheets, A3/A4R 40 sheets, <Coated media> 2 sheets
 Power Source: From the main unit
 Dimensions (W x D x H): 527 (Max 656*) x 623 x 1,099 (Max 1,195*) mm
 *when the auxiliary tray is extended.

Weight: Approx. 36 kg
 Tray Capacity / Paper Weight / Staple Position / Staple Capacity: same as STAPLE FINISHER-AC1 but if there are any sheets on the saddle tray, the capacity of Tray A becomes limited to 1,500 sheets
 Booklet Stitch Paper Size: A3, A4R, B4, Custom size (195 x 270 mm to 304.8 x 457.2 mm)
 Booklet Stitch Paper Weight: Body sheet 52-220 gsm, Cover sheet 52-256 gsm
 Booklet Stitch Staple Capacity (including 1 cover sheet): <Non coated media> 20 sheets (52-81.4 gsm), 10 sheets (82-105 gsm), 5 sheets (106-150 gsm), 4 sheets (151-209 gsm), 3 sheets (210-220 gsm), <Coated media> 5 sheets (85-150 gsm), 4 sheets (151-209 gsm), 3 sheets (210-220 gsm)
 Non Staple Folded Bunch Capacity: <Non coated media> 3 sheets (52-105 gsm), 1 sheet (106-256 gsm), <Coated media> 1 sheet
 Power Source: From the main unit
 Dimensions (W x D x H): 527 (Max 656*) x 623 x 1,099 (Max 1,195*) mm
 *when the auxiliary tray is extended.

Staple Finisher-AG1

Requires the [Accessory Interface Kit-A2](#)
 Tray Capacity (with 80 gsm paper):
 Upper Tray: SRA3, A3, A4, A4R, A5R, A5, A6R, B4, B5, B5R: 1,000 sheets (64 to 324gsm), 200 sheets (325 to 350gsm)
 Lower Tray: A4, B5: 2,000 sheets (64 to 324 gsm), 400 sheets (325 to 350 gsm)
 SRA3, A3, A4R, B4: 1,000 sheets (64 to 324 gsm), 200 sheets (325 to 350 gsm)
 B5R: 1,000 sheets (64 to 324 gsm), 400 sheets (325 to 350gsm)
 Lower Tray (High capacity loading mode): A4, B5: 4,000 sheets, A4R, B5R : 2,000 sheets
 A3, B4 : 1,500 sheets
 SRA3 : 1,000 sheets
 Paper Weight: 52 to 350 gsm
 Staple Position: Corner, Double
 Staple Capacity (including Staple On Demand): A4/B5: 100 sheets (52 to 80 gsm)
 A3/A4R/B4/B5R: 50 sheets (52 to 81.4 gsm)
 Power supply: 220-240V/8A 50/60Hz
 Dimensions (W x D x H): 860 x 792 x 1,239 mm (when the extension tray is extended)
 Weight: Approx. 130 kg

Booklet Finisher-AG1

Requires the [Accessory Interface Kit-A2 \(PCB unit\)](#) (Includes the above Staple Finisher-AG1 basic staple specifications)
 Saddle Stitch paper size: SRA3, A3, A4R, B4, Custom size (210.0 x 279.4 mm to 330.2 x 487.7 mm)
 Saddle Stitch Staple Capacity: 25 sheets (52 to 80 gsm) (including 1 cover sheet)
 Power supply: 220-240V/8A 50/60Hz
 Dimensions (W x D x H): 1,060 x 792 x 1,239 mm (when the extension tray is extended)
 Weight: Approx. 180 kg

4 Hole Puncher Unit-A1

Requires either the [STAPLE FINISHER-AC1](#) or [BOOKLET FINISHER-AC1](#)
 4 Holes (SWE)
 Paper Weight: 52-300 gsm
 Paper Size: A3, A4, A4R, B4, B5, B5R
 Power Source: From the finisher

Puncher Unit-BT1 (2/F4H)

Requires either the [STAPLE FINISHER-AG1](#) or [BOOKLET FINISHER-AG1](#)
 2 or 4 Holes (FRN)
 Paper Weight: 52-300 gsm
 Paper Size: 2 holes A3, A4, A4R, A5L, B4, B5, B5R, Custom size (182 x 182 mm to 297 x 432.0 mm excluding 203 x 257 mm to 297 x 270 mm); 4 holes A3, A4, B4, B5, Custom size (257 x 182 mm to 297 x 432 mm)
 Power Source: From the finisher

Puncher Unit-BU1 (S4H)

Requires either the [STAPLE FINISHER-AG1](#) or [BOOKLET FINISHER-AG1](#)
 4 Holes (SWE)
 Paper Weight: 52-300 gsm
 Paper Size: A3, A4, A5L, B4, B5, Custom size (257 x 182 mm to 297 x 432 mm)
 Power Source: From the finisher

Document Insertion Unit-R1

Requires either the [Staple Finisher-AG1](#) or [Booklet Finisher-AG1](#)
 Number of trays: 2
 Tray Capacity: Up to 100 Sheets (with 80 gsm paper)
 Upper tray: up to 200 sheets
 Lower tray: up to 200 sheets
 Acceptable Paper Type: Thin, Plain, Recycled, Color, Heavy, Coated, Textured, Bond, Pre-punched, Letterhead, Tab
 Acceptable Paper Sizes: SRA3, A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R
 Acceptable Paper Weight: 52 to 300 gsm
 Power Source: 100-240V/50/60Hz 1.0A
 Dimensions (W x D x H): 336x 793 x 1,407 mm (attached to the device: width excluding document tray)
 Weight: Approx. 61 kg

Paper Folding Unit-K1

Requires either the [Staple Finisher-AG1](#) or [Booklet Finisher-AG1](#)
 Supported Folding Type: Z-Fold, C-Fold, Accordion-Z-Fold, Double Parallel-Fold, Half-Fold
 Acceptable Paper Type: Thin, Plain, Recycled, Color, Bond
 Acceptable Paper Sizes:
 Z-Fold: Thin, Plain, Recycled, Color: A3,A4R,B4
 C-Fold/Accordion-Z-Fold/Double Parallel-Fold/Half-Fold: A4R
 Acceptable Paper Weight:
 Z-Fold/ C-Fold/Accordion-Z-Fold/Half-Fold: 52 to 105 gsm
 Double Parallel-Fold: 52 to 90 gsm
 Power Source: from the finisher
 Dimensions (W x D x H): 336 x 793 x 1,190 mm (attached to the device)
 Weight: Approx. 71 kg

2/4 Hole Puncher Unit-A1

Requires either the [Staple Finisher-AC1](#) or [Booklet Finisher-AC1](#)
 Two or Four Holes
 Acceptable Punch Paper Weight: 52 to 300 gsm
 Acceptable Punch Paper Size:
 Two holes A3, A4, A4R, A5, B4, B5, B5R
 Four holes A3, A4
 Power Source: From the finisher

Booklet Trimmer-G1

Requires [Booklet Finisher-AG1](#)
 Acceptable Paper Size: Standard size: SRA3, A3, A4R, B4
 Custom size: 210.0x279.4 mm to 330.2x487.7 mm
 Waste Tray Capacity: approx. 5,000 sheets
 Acceptable Paper Weight: 52 to 220 gsm
 Trim Amount: 2 to 28mm
 Power Source: from the finisher
 Dimensions (W x D x H): 1,933 x 794 x 1,044 mm (attached to the device: width excluding belt conveyer)
 Weight: Approx. 152 kg

Document Insertion/Folding Unit-K1

Requires either the [Staple Finisher-AC1](#) or [Booklet Finisher-AC1](#)
 Number of trays: 1
 Supported Folding Type: Z-Fold, C-Fold
 Acceptable Paper Type:
 Insertion Unit: Thin, Plain, Recycled, Color, Heavy, Coated, Textured, Bond, Letterhead, Tab
 Z-Fold/C-Fold: Thin, Plain, Recycled, Color
 Acceptable Paper Sizes:
 Insertion Unit: SRA3, A3, A4, A4R, B4, B5, B5R
 Z-Fold: A3, A4R, B4
 C-Fold: A4R
 Acceptable Paper Weight:
 Insertion Unit: 60 to 256 gsm
 Z-Fold/C-Fold: 60 to 105 gsm
 Tray Capacity (with 80 gsm paper):
 Insertion: Up to 100 Sheets
 Z-Fold*: A3, B4: 30 sheets
 A4R: 10 sheets
 C-fold: A4R: 40 sheets

*Z-Fold output to the Staple Finisher-AC1 or Booklet Finisher-AC1
 Power Source: 100-240V/50/60Hz 1.0A
 Dimensions (W x D x H): 247 x 679 x 1,242 mm (attached to the device: width excluding document tray)
 Weight: Approx. 76 kg



TECHNICAL SPECIFICATIONS

imagePRESS C270 Series

HARDWARE ACCESSORIES

Card Readers

COPY CARD READER-F1 - Magnetic physical card access system. (Integrates with Department ID, not for use with uniFLOW)

COPY CARD READER ATTACHMENT-A4 - Attachment kit for COPY CARD READER-F1.

Others

Utility Tray-B1
Printer Cover-H2
Tab Feeding Attachment-F1
Numeric Keypad-A2
Accessory Interface Kit-A2
Finisher Jogger Kit-A1
Side Guide Plate Fixing Bracket-A1
Envelope Feeder Attachment-H1
Envelope Feeder Attachment-F1
Envelope Feeder Attachment-G1
Stack Bypass Alignment Tray-D1
Long Sheet Tray-B1
Paper Deck Path Kit-B1
Finisher Long Sheet Catch Tray-B1
Inserter Option controller Kit-A1

SECURITY OPTIONS

Data Security

Memory Mirroring Kit-A1
1TB SSD-A1
250GB SSD-A1

SYSTEM & CONTROLLER OPTIONS

Print Accessories

PCL International Font Set-A1
imagePRESS PS Printer Kit-G1

Barcode Printing

BARCODE PRINTING KIT-D1 - Provides the ability to print 1D and 2D barcodes on output using jet caps technology.

EFI-Fiery Based Controller

imagePRESS Server M20

EFI-Fiery Based Controller Options

Fiery Impose
Fiery Compose
Fiery Impose and Compose

SYSTEM ACCESSORIES

Copy Control Interface Kit-A1
Connection Kit-A4 for Bluetooth LE
Serial Interface Kit-K3

FAX ACCESSORIES

Super G3 FAX Board-AX1
Remote Fax Kit-A1
IP FAX Expansion Kit-B1

OTHER OPTIONS

Accessibility Accessories

ADF Access Handle-A1
Voice Guidance Kit-G1
Voice Operation Kit-D1

Staple Cartridges

Staple-N1
Staple-P1
Staple Cartridge-X1
Staple Cartridge-Y1

Antimicrobial Film

Copy Card Reader Attachment-A5

Software & Solutions



Certifications and compatibility



Canon Inc.
canon.com

Canon Europe
canon-europe.com

English edition

© Canon Europa N.V., 2022